

SINCE 1935
VARUNA[®]
RAISE • REACH • REAP



Highest Star Rated Pumps in INDIA



V4 OF & WF

SUITABLE FOR 100 mm BOREWELL OR ABOVE (Min.Bore Dia. 100mm)

APPROXIMATE PERFORMANCE CHART AT 2880 RPM, 200-240 VOLTS SINGLE PHASE / 380-415 VOLTS THREE PHASE, 50 Hz. A.C. SUPPLY.

Maximum Motor OD :- 96.5mm & Pump OD :- 98 mm

Stainless Steel Submersible Pumpsets

OUTLET SIZE :- 32mm

TYPE OF FLOW : RADIAL

MODEL		MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM						
OF	WF	KW	H.P.			0	20	25	30	35	40	50
VPO 2A	VP 2A	0.37	0.50	6		36	32	29	26	23	16	11
VPO 2A	VP 2A	0.37	0.50	9		53	48	44	38	34	24	17
VPO 2A	VP 2A	0.55	0.75	13		77	69	64	55	49	35	24
VPO 2A	VP 2A	0.75	1.00	18		107	95	88	77	68	48	34
VPO 2A	VP 2A	1.10	1.50	23		136	122	112	98	87	62	43
VPO 2A	VP 2A	1.50	2.00	28		166	148	137	119	106	75	52
VPO 2A	VP 2A	1.50	2.00	33		195	175	161	140	125	89	62
VPO 2A	VP 2A	2.20	3.00	40		240	213	193	173	153	107	73
VPO 2A	VP 2A	2.20	3.00	48	288	256	232	208	184	128	88	

OUTLET SIZE :- 32mm

TYPE OF FLOW : RADIAL

MODEL		MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM						
OF	WF	KW	H.P.			0	25	30	40	50	70	75
VPO 3A	VP 3A	0.37	0.50	6		38	34	33	31	27	18	15
VPO 3A	VP 3A	0.55	0.75	9		57	51	50	46	41	27	23
VPO 3A	VP 3A	0.75	1.00	12		76	68	66	61	54	36	31
VPO 3A	VP 3A	1.10	1.50	15		95	85	83	77	68	44	39
VPO 3A	VP 3A	1.10	1.50	18		113	102	99	92	82	53	46
VPO 3A	VP 3A	1.50	2.00	22		139	125	121	112	100	65	57
VPO 3A	VP 3A	1.50	2.00	25		158	142	138	128	114	74	64
VPO 3A	VP 3A	2.20	3.00	29		183	164	160	148	132	86	75
VPO 3A	VP 3A	2.20	3.00	33	208	187	182	169	150	98	85	

OUTLET SIZE :- 38mm

TYPE OF FLOW : RADIAL

MODEL		MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM						
OF	WF	kW	H.P.			0	31	48	68	85	100	112
VPO 5A	VP 5A	0.37	0.50	4		26	23	21	19	16	12	8
VPO 5A	VP 5A	0.55	0.75	6		39	35	32	29	24	18	12
VPO 5A	VP 5A	0.75	1.00	8		52	46	42	38	32	24	16
VPO 5A	VP 5A	0.75	1.00	10		65	58	53	48	40	30	20
VPO 5A	VP 5A	1.10	1.50	12		78	69	66	57	48	36	24
VPO 5A	VP 5A	1.50	2.00	17		111	98	89	81	68	51	34
VPO 5A	VP 5A	2.20	3.00	21		137	121	110	100	84	63	42
VPO 5A	VP 5A	2.20	3.00	25		163	144	131	119	100	76	50

OUTLET SIZE :- 50mm

TYPE OF FLOW : RADIAL

MODEL		MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM						
OF	WF	kW	H.P.			0	34	68	100	135	168	184
VPO 8A	VP 8A	0.75	1.00	5		30	28	25	23	21	16	12
VPO 8A	VP 8A	1.10	1.50	7		42	39	35	32	29	22	17
VPO 8A	VP 8A	1.50	2.00	10		60	55	50	46	41	31	24
VPO 8A	VP 8A	2.20	3.00	12		72	66	60	55	49	37	29
VPO 8A	VP 8A	2.20	3.00	15		90	83	75	69	62	47	36

V6**SUITABLE FOR 150mm BOREWELL OR ABOVE (Min. Bore Dia. 150mm)**

APPROXIMATE PERFORMANCE CHART AT 2880 RPM, 380-415 VOLTS THREE PHASE, 50 Hz. A.C. SUPPLY.

Maximum Motor OD :- 142 mm & Pump OD. :- 142 mm

Stainless Steel Submersible Pumpsets

OUTLET SIZE :- 50mm

TYPE OF FLOW : Mixed

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM						
	WF	KW			H.P.	0	100	132	160	220	270
VP 10A	2.20	3.00	6		63	59	54	50	46	40	28
VP 10A	2.20	3.00	7		73	68	63	58	53	46	32
VP 10A	3.00	4.00	10		104	98	90	83	76	66	46
VP 10A	3.70	5.50	14		146	137	127	117	106	92	64
VP 10A	5.50	7.50	15		156	146	136	125	114	99	69
VP 10A	5.50	7.50	18		188	176	163	150	137	119	83
VP 10A	7.50	10.00	20		208	195	181	167	152	132	92
VP 10A	7.50	10.00	24		250	234	217	200	182	158	110
VP 10A	7.50	10.00	27	281	263	244	225	205	178	124	
VP 10A	9.30	12.50	30	313	293	271	250	228	198	138	
VP 10A	11.00	15.00	36	375	351	326	300	273	237	165	

OUTLET SIZE :- 50mm

TYPE OF FLOW : Mixed

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM						
	WF	KW			H.P.	0	100	135	160	202	254
VP 10D	5.50	7.50	20		211	197	184	167	151	127	91
VP 10D	5.50	7.50	24		254	237	221	200	182	153	109
VP 10D	7.50	10.00	27		285	266	248	225	204	172	122
VP 10D	7.50	10.00	30		317	296	276	250	227	191	136

OUTLET SIZE :- 65mm

TYPE OF FLOW : Mixed

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM							
	WF	kW			H.P.	0	102	135	168	201	235	266
VP 15A	2.20	3.00	5		53	50	48	45	43	38	33	30
VP 15A	3.00	4.00	7		74	70	67	63	60	53	46	42
VP 15A	3.70	5.00	9		95	90	86	81	77	68	59	54
VP 15A	5.50	7.50	13		137	130	124	117	111	98	86	78
VP 15A	7.50	10.00	18		189	180	172	162	153	136	119	108
VP 15A	9.30	12.50	21		221	210	200	189	179	158	139	126
VP 15A	11.00	15.00	27		284	270	258	242	230	204	178	163

OUTLET SIZE :- 65mm

TYPE OF FLOW : Mixed

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM						
	WF	kW			H.P.	0	150	200	250	300	333
VP 17A	2.20	3.00	5		57	54	50	46	41	34	27
VP 17A	3.00	4.00	6		68	65	60	55	49	40	32
VP 17A	3.70	5.00	8		91	87	80	73	65	54	43
VP 17A	5.50	7.50	9		102	97	91	82	73	60	48
VP 17A	5.50	7.50	12		136	130	121	110	98	80	64
VP 17A	7.50	10.00	16		181	173	161	147	130	107	85
VP 17A	9.30	12.50	20		226	217	201	183	163	134	107
VP 17A	11.00	15.00	24		272	260	241	220	195	161	128

OUTLET SIZE :- 75mm

TYPE OF FLOW : Mixed

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM							
	KW	H.P.			0	202	270	335	405	470	535	652
VP 30A	2.2	3.0	2		23	21	20	19	18	16	14	9
VP 30A	3.0	4.0	3		34	32	30	28	27	24	21	13
VP 30A	3.7	5.0	4		46	43	40	38	35	32	28	17
VP 30A	3.7	5.0	5		57	54	50	47	44	40	35	22
VP 30A	5.5	7.5	6		68	64	60	57	53	48	42	26
VP 30A	5.5	7.5	7		80	75	71	66	62	57	49	30
VP 30A	5.5	7.5	8		91	86	81	76	71	65	56	35
VP 30A	7.5	10.0	9		103	96	91	85	80	73	63	39
VP 30A	9.31	2.5	10		115	105	100	95	90	80	70	45
VP 30A	9.31	2.5	11		127	116	110	105	99	88	77	50
VP 30A	9.31	2.5	12		137	128	121	114	106	97	84	52
VP 30A	11.0	15.0	12		137	128	121	114	106	97	84	52
VP 30A	11.0	15.0	13		148	139	131	123	115	105	91	56

V6

SUITABLE FOR 150mm BOREWELL OR ABOVE (Min. Bore Dia. 150mm)

APPROXIMATE PERFORMANCE CHART AT 2880 RPM, 380-415 VOLTS THREE PHASE, 50 Hz. A.C. SUPPLY.

Maximum Motor OD :- 142 mm & Pump OD. :- 147 mm

Stainless Steel Submersible Pumpsets

OUTLET SIZE :- 75 mm (ON DEMAND CAN PROVIDE 100mm)

TYPE OF FLOW : MIXED

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM								
	KW	H.P.			0	252	420	585	670	750	835	920	1000
VP 46A	3.0	4.0	2		27	25	23	21	19	18	16	13	11
VP 46A	3.7	5.0	3		41	38	35	31	29	26	23	20	16
VP 46A	4.5	6.0	3		41	38	35	31	29	26	23	20	16
VP 46A	5.5	7.5	4		54	50	46	41	38	35	31	26	21
VP 46A	7.5	10.0	5		68	63	58	52	48	44	39	33	26
VP 46A	9.31	2.5	6		81	75	69	62	58	53	47	40	32
VP 46A	9.31	2.5	7		95	88	81	72	67	61	54	46	37
VP 46A	11.0	15.0	8		108	100	92	82	77	70	62	53	42

OUTLET SIZE :- 75 mm (ON DEMAND CAN PROVIDE 100mm)

TYPE OF FLOW : MIXED

MODEL	MOTOR RATING		STAGE	HEAD IN METERS	DISCHARGE IN LPM							
	KW	H.P.			0	335	502	670	835	1000	1168	1300
VP 60A	3.7	5.0	2		29	27	24	21	18	16	12	8
VP 60A	5.5	7.5	3		43	40	36	32	28	24	18	13
VP 60A	7.5	10.0	4		57	53	48	42	37	32	25	17
VP 60A	9.31	12.5	5		72	66	60	53	46	40	31	21
VP 60A	11.0	15.0	6		86	80	72	64	55	47	37	25
VP 60A	11.0	15.0	7		100	93	84	74	65	55	43	30



Mounting The Footprints Globally



La-Gajjar
MACHINERIES PVT. LTD.
An ISO 9001 : 2015 Company

LA-GAJJAR MACHINERIES PVT. LTD. Acidwala Estate, Nagarwel Hanuman Road, Amraiwadi, Ahmedabad - 380 026
Phone: +91- 79- 22777485/87/89 | T oll free: 1800 258 2565 | www.varunapumps.com | crm@lgmindia.com